

# **ARDEX Catalyst Spray**

## **Adhesive Activator**

Accelerator for use with

ARDEX WPM 179 – Single Part Rubber Membrane

ARDEX AF 241 – Carpet Adhesive

ARDEX AF 266 – Outdoor Grass Carpet Adhesive

ARDEX WPM 750 – Undertile Butynol adhesive



ARDEX Australia Pty Ltd 20 Powers Road Seven Hills NSW 2147 Tel: (02) 9851 9199

Fax: (02) 9674 5621

Email: techinfo@ardexaustralia.com

Internet: www.ardex.com

ARDEX New Zealand Ltd 32 Lane St, Woolston Christchurch, New Zealand Tel: (03) 373 6900 Fax: (03) 384 9779

Email: techinfo@ardexaustralia.com

Internet: www.ardex.com

## **ARDEX Catalyst Spray**

### **Adhesive Activator**

#### **DESCRIPTION**

ARDEX Catalyst Spray with the use of Speedtec technology is a clear solution which when applied to nominated ARDEX Adhesives accelerates the tack time for quicker installation of floor coverings.

#### **FEATURES**

ARDEX Catalyst Spray is designed to increase initial tack for ARDEX Adhesives with ARDEX Speedtec – Technology. ARDEX Catalyst Spray also acts as an innate film formation for ARDEX WPM 179 – Single Component Rubber Membrane.

#### **AREAS OF APPLICATION**

Internal and external floors and walls. ARDEX Catalyst Spray is used to increase initial tack on nominated ARDEX Flooring Adhesives and ARDEX WPM 179.

#### **NOMINATED ADHESIVES**

ARDEX AF 266, AF 241 Adhesives
ARDEX WPM 750 Adhesive
ARDEX WPM 179 Rubber Membrane

#### **APPLICATION**

With the spray bottle spray a fine mist evenly across the adhesive to one side only; as soon this is complete install the following floor coverings to the treated adhesive.

#### **SAFETY PHRASES**

This product is considered non-hazardous and non-toxic in normal usage.

Avoid contact with skin and eyes; in case of contact with the eyes, rinse immediately with plenty of water and seek medical advice; wear suitable gloves and eye protection and keep the product out of the reach of children. If swallowed do not induce vomiting, give a glass of water and contact a doctor. For further material safety data, consult the latest Material Safety Data Sheet.

#### **TECHNICAL DATA**

**Raw material**: Proprietary solution

Clean with: Water

**Packaging:** 500ml spray bottle

**Storage:** Store in a cool dry space,

12 months shelf life in un-opened containers

#### **GUARANTEE**

Ardex Australia Pty Ltd ("we" or "us") guarantees this product ("our goods") is free from manufacturing defects and will perform to any applicable specification published by us for 10 years from the date of purchase. Our liability under this guarantee is limited at our option to replacement of the product, repair of any damage to the immediate surface or area of application of the product, or compensation, in each case if we are satisfied loss or damage was due to a breach of this guarantee. This guarantee does not apply if damage or loss is due to failure to follow published instructions or any act or circumstance beyond our control, including shade variations and efflorescence. If you wish to make a claim under this guarantee you must notify us (Ardex Australia Pty Ltd, 20 Powers Road Seven Hills NSW 2147; Toll Free: 1800 224 070; Email: techinfo@ardexaustralia. com) and provide evidence of your purchase of the product within 30 days of any alleged loss or damage occurring. We reserve the right to ask you for satisfactory evidence of any alleged loss or damage. Any claim under this guarantee is at your cost. This guarantee is in addition to any rights or remedies you may have as a "consumer" under the Australian Consumer Law and to that extent you need to be aware that: "Our goods come with guarantees that cannot be excluded under the Australian Consumer Law. You are entitled to a replacement or refund for a major failure and for compensation for any other reasonably foreseeable loss of damage. You are also entitled to have the goods repaired or replaced if the goods fail to be of acceptable quality and the failure does not amount to a major failure".

**Note:** ARDEX products are generally warranted for 10 years when installed to the relevant Australian Standards and applicable ARDEX specifications, technical data sheet and instruction for application and use. While we assure customers the high standard and quality of our products and services, we accept no liability for any loss or damage which arises from particular site conditions, poor handling and storage, or installation by unqualified and unskilled applicators.

#### DISCLAIMER

The technical details, recommendations and other information contained in this data sheet are given in good faith and represent the best of our knowledge and experience at the time of printing. It is your responsibility to ensure that our products are used and handled correctly and in accordance with any applicable Australian Standard, our instructions and recommendations and only for the uses they are intended. We also reserve the right to update information without prior notice to you to reflect our ongoing research and development program. Country specific recommendations, depending on local standards, codes of practice, building regulations or industry guidelines, may effect specific installation recommendations. The supply of our products and services is also subject to certain terms, warranties and exclusions, which may have already been disclosed to you in prior dealings or are otherwise available to you on request. You should make yourself familiar with them.

#### © ARDEX Australia Pty Ltd 2012.

All aforementioned products are the trade marks of ARDEX Australia Pty Ltd, its licensors and affiliates.

#### ARDEX Australia Pty Ltd

Technical Services Toll Free: 1800 224 070

 New South Wales
 Ph (02) 9851 9100

 Queensland
 Ph (07) 3817 6000

 Victoria/Tasmania
 Ph (03) 8339 3100

 South Australia
 Ph (08) 8406 2500

 Western Australia
 Ph (08) 9256 8600

#### **ARDEX New Zealand Ltd**

 Technical Services Toll Free: 0800 227 339

 Auckland
 Ph (09) 580 0005

 Wellington
 Ph (04) 568 5949

 Christchurch
 Ph (03) 373 6900